

Product-/datasheet Bambus Ekstrem™ Tongue & groove

Technical service

Manufacturer	Holse & Wibroe A/S
Vat no.	CVR-nr. 28281439
Address	Agenavej 16, 2670 Greve
Phone	+45 88 18 28 00
E-mail	Info@holseogwibroe.dk
Web-address	www.holseogwibroe.dk

Specifications

Item numbers Thickness Width Length Density Reaction to fire Emission of formaldehyde Thermal conductivity Durability Package content Weight/Package Construction Mechanic Bevel	110404, 115404 14 mm, ±0,20 mm 142 mm, ±0,20 mm 1830 mm, ±0,50 mm Approx. 1.050 kg/ Cbm D _{fi,s1} E1 0,24 W/mK Class 1 1,98 sqm. Approx 29 Kg. Solid Tongue & groove 4 sides Micro	EN 14342:2005+A1:2008
If not mentioned, standards are accordingly to EN 14342		

Surface treatment

Lacquer	Lacquered 5 times with BONA-UV matt lacquer (Natural). Gloss 6-8 Minor repairs before lacquer may occur.
Oil	Treated 3 times with WOCA hardening natural oil. Smaller cracks may occur in the surface due to the compression. Before usage, the surface should be sanded with the supplied "Net 180" and then oiled 1 time with WOCA maintenance oil.

Installation & Maintenance

Installation	To be installed fully glued or floating. Always check latest updated version at www.holseogwibroe.dk
Maintenance & Care	Check latest version at www.holseogwibroe.dk

January 2023