

## Product-/datasheet Bambus LamelPlank™ Click

### Technical service

Manufacturer	Holse & Wibroe A/S
Vat no.	CVR-nr. 28281439
Address	Agenavej 16, 2670 Greve
Phone	+45 88 18 28 00
E-mail	<a href="mailto:Info@holseogwibroe.dk">Info@holseogwibroe.dk</a>
Web-address	<a href="http://www.holseogwibroe.dk">www.holseogwibroe.dk</a>

### Specifications

Item numbers	120603, 125203, 125303, 125503, 125603
Thickness	3/14 mm, ±0,2 mm
Width	190 mm, ±0,2 mm
Length	1900 mm, ±2 mm
Density	Ca. 640 kg/ Cbm
Reaction to fire	C <sub>fi</sub> -s1 – (EN 13501-1:2018 with clause 12.5 & 12.9)
Emission of formaldehyde	E1
Thermal conductivity	0,14 W/mK
Durability	Class 1
Package content	2,89 sqm.
Weight/Package	Approx 27 Kg.
Construction	3 mm Vertical bamboo top layer, 11 mm solid plywood core.
Mechanic	Click 4 sides Micro

### Surface treatment

Lacquer	Lacquered 5 times with BONA-UV matt lacquer (Natural or White). Gloss 6-8. Minor repairs before lacquer may occur.
Oil	Treated 3 times with with WOCA hardening oil (natural or White). Before usage the surface should be treated with one-time WOCA maintenance oil.

## Installation & Maintenance

Installation	To be installed floating. Always check latest updated version at <a href="http://www.holseogwibroe.dk">www.holseogwibroe.dk</a>
Maintenance & Care	Check latest updated version at <a href="http://www.holseogwibroe.dk">www.holseogwibroe.dk</a>

July 2023